

DeoxIT[®] D5 Spray, D-Series Contact Rejuvenator, Lubricant and Protectant

1. Part No.:

D5S-6-LMH (NSN 6850-01-435-6476)

2. Container Size:

142 g (5.0 oz.), with Low-Med-High Valve

3. Product Description:

Unique contact treatment, rejuvenator, conductivity enhancer and lubricant. Removes oxidation and corrosion on metal surfaces. Fills in microscopic gaps and reseals surface for better contact to enhance flow of electricity. Chemically improves metal-to-metal connections and contacts. Improves connector performance/reliability. Temperature* range: -34 to +200°C.

4. Features/Benefits:

5% Spray, Flushing action, Safe on most plastics.

DeoxIT[®] D100L concentrate has approximately 20% chemical deoxidizing action.

Excellent deoxidizing, good protection, no ozone depletion.

Improves conductivity and reduces intermittent connections.

Reduces arcing, RFI, wear and abrasion.

Cleaner Audio - Clearer Video - Reliable Data.

5. Formulation:

5% DeoxIT[®] D100L
75% Odorless mineral spirits (CAS 64742-88-7)
20% DIFLUOROETHANE (CAS 75-37-6)



6. Which DeoxIT[®] product do I Use:

- ▶ Use **DeoxIT[®] D-Series** contact treatment on surfaces that have been in service or have visual signs of oxidation. Contains 20% active deoxidizer.
- ▶ Use **DeoxIT[®] Gold G-Series** conditioner on new surfaces, and gold plated surfaces. Ideal for preventing dendrite/fretting corrosion. Protects both surface and base metals. Ideal for critical applications. Contains >1% active deoxidizer.
- ▶ Use **DeoxIT[®] Shield S-Series** to protect surfaces from severe environments (humidity, salts, pollutants, sulfur, etc.). Use on clean surface. Contains 0% active deoxidizer.

* **NOTE:** Temperature ranges may vary depending on conditions.
On critical applications, independent testing is highly recommended.





Audio/Video



Computers



Automotive



Communications



Marine



Electrical



Energy



Photography



Security



Medical



Avionics

7. Directions for Use:

1. Turn off, unplug the device.
2. Apply one short burst of DeoxIT® D-Series contact treatment to contact/connector surface. Operate the part/device to help break up oxides and contamination. Wait a few seconds, reapply one short burst. Wait two minutes before turning on equipment. **Test for compatibility before use.**
3. In extreme cases (severe oxidation or corrosion), you may need to leave DeoxIT® on overnight. If that is necessary; apply, then the following day remove any contaminants lifted by DeoxIT® with a lint free swab or cloth on accessible surfaces (If surface is not accessible, repeat step two above.). When surface is deoxidized (no residue on the swab/cloth), finish with a short burst of DeoxIT®, then remove excess leaving a thin layer.
4. If you notice a green or black coloration on the surface (may take a few days) after applying DeoxIT®, this indicates dissolved oxidation (surface was severely oxidized). Follow step "2" above one more time.
5. **For extended protection:** After surface is deoxidized, apply DeoxIT® Gold G-Series for indoor applications or DeoxIT® Shield S-Series for outdoor applications.
6. **NOTE:** To prevent overspray or spraying in unwanted areas, you can always spray onto a lint-free swab or cloth first and then using the swab/cloth apply the DeoxIT® to the connector/contact surface(s).

8. Other Applicators:

| Part No. | % DeoxIT® | VOC (%) | Applicator | Size | Flammable/Nonflammable |
|--------------------------|-----------|---------|------------------|------------|------------------------|
| DN5S-6N | 5% | 0% | spray | 163 g | nonflammable |
| DN5S-2N | 5% | 0% | mini-spray | 40 g | nonflammable |
| D100S-2 | 100% | 0% | spray | 57g | nonflammable |
| D100P | 100% | 0% | pen | 6 mL | nonflammable |
| D100L-P6C | 100% | 0% | oiler pen | 6 mL | nonflammable |
| D50W | 100% | 0% | wipes | 50 count | nonflammable |
| D1W | 100% | 0% | wipes | individual | nonflammable |
| D100L-2C | 100% | 0% | tube | 2 mL | nonflammable |
| D100L-2DB | 100% | 0% | brush bottle | 7.4 mL | nonflammable |
| D100L-25C | 100% | 0% | needle dispenser | 25 mL | nonflammable |
| D100L (bulk, many sizes) | 100% | 0% | bottle/drum | assort. | nonflammable |

9. Product Selection Guides:

DeoxIT® - Product Selection Guide

| | DeoxIT® D-Series | DeoxIT® Gold G-Series | DeoxIT® Gold GxL Gx-Series | DeoxIT® Gold Gx2 Gx2-Series | DeoxIT® Shield S-Series | DeoxIT® Fader F-Series |
|-----------------------------------|---------------------|-----------------------------|----------------------------------|-----------------------------------|-------------------------------|------------------------------|
| New Surfaces | | ✓ | ✓ | ✓ | ✓ | ✓ |
| * In Service / Used | ✓ | | | | | ✓ |
| Gold surfaces | | ✓ | ✓ | ✓ | | |
| Oxidation / corrosion visible | ✓ | | | | | |
| Conductive plastics | | | | | | ✓ |
| ** Outdoor / Severe environments | ✓ | | | | | ✓ |
| Deoxidizing / cleaning properties | 20% | 0.1% | 0.1% | 0.0% | 0.0% | 0.0% |
| Metal / Plastic surfaces | Yes | Yes | Yes | Yes | Yes | |
| Plastics compatibility | Excellent | Excellent | Excellent | Excellent | Excellent | Excellent |
| Temperature range (°C) | -34/200 | -45/200 | -45/240 | -45/300 | -34/210 | -26/150 |
| Stationary & moving surfaces | Yes | Yes | Yes | Yes | Yes | Yes |
| Seals & protects surface metal | Good | Excellent | Excellent | Excellent | Good | No |
| Seals & protects base metals | Fair | Excellent | Excellent | Excellent | Fair | No |

✓ All products are Nonflammable and RoHS Compliant

* In Service: Clean with DeoxIT® D-Series. For added protection, follow with DeoxIT® Gold (indoors), DeoxIT® Shield (outdoors) or DeoxIT® Grease (additional barrier).

DeoxIT® - Spray Selection Guide

| Product Series | FP | QD | NF | PC | VOC |
|--|----|----|----|----|--------------|
| Standard - 5% solution | ✓ | | | ✓ | 75% (588g/L) |
| D5S-6, D5MS-15, G5S-6, G5MS-15, S5S-6, S5MS-15, F5S-6, F5MS-15 | | | | | |
| N Series - 5% solution | | ✓ | ✓ | ✓ | 0.0% |
| DN5S-6N, DN5S-2N, GN5S-6N, GN5S-2N, SN5S-6N, SN5S-2N | | | | | |
| X Series - 5% solution | | ✓ | ✓ | ✓ | 0.0% |
| GX5S-6N | | | | | |
| 100% Spray solution | | | ✓ | ✓ | 0.0% |
| D100S-2, G100S-2, F100S-L2 | | | | | |

FP = Flushing properties QD = Quick dry / non drip

NF = Nonflammable PC = Plastics compatibility VOC = VOC (%)



Audio/Video



Computers



Automotive



Communications



Marine



Electrical



Energy



Photography



Security



Medical



Avionics

10. Materials Compatibility (Plastics, Rubber, Elastomeric and Metals):

(Rating: Not compatible, Poor, Fair, Good, Excellent), (N/A = Not applicable (no solvents and propellants)

(* If the product is not 100% DeoxIT® then the package is rated before and after the solvents/propellants are applied to materials. Compatibility testing is always recommended)

| Material Name | Rating (*100% DeoxIT®) | Rating (*with solvents) |
|--------------------|------------------------|-------------------------|
| ABS | Excellent | Fair-Good |
| Nylon | Excellent | Excellent |
| Lexan | Excellent | Excellent |
| HDPE | Good | Good |
| LDPE | Good | Good |
| C.E.Phenolic | Excellent | Good |
| Epoxy | Excellent | Excellent |
| Polycarbonate | Excellent | Fair-Good |
| PMMA | Fair | Fair |
| POM | Excellent | Excellent |
| PP | Excellent | Good |
| PS | Fair | Fair |
| PTFE | Excellent | Excellent |
| PVC | Excellent | Excellent |
| TPE/Rubber/Varnish | Poor | Poor |

IMPORTANT:

Rating, 100% DeoxIT®: Any of the above that fall into the “Fair” and “Poor” categories should be thoroughly tested for compatibility. They may be compatible, however, it will depend on the manufacturing process of the materials. Acrylics, ABS, and polycarbonate, if under stress, may show slight cracking or crazing damage. Test for compatibility before use. On porous materials; i.e. wood, rubber, cloth, some phenolics, semi-cured materials, no liquid or solvents should be used. Occasionally, DeoxIT® will get onto unwanted surfaces, quickly wipe off surface and usually no damage will occur.

Rating, with solvents: Similar to rating above (100% DeoxIT®). However, any rating worse than the 100% DeoxIT® may require additional care. If DeoxIT is applied to unwanted areas or materials, wipe off surface quickly and usually no damage will occur. Alternatively, apply DeoxIT® onto a lint-free swab or cloth first and then wipe onto desired metal surface.

11. DeoxIT® Essential Reference:

DeoxIT® D-Series - Brings old systems back to life!


DeoxIT® Gold G-Series - Maintains new system performance!

DeoxIT® Shield S-Series - Maintains new system performance for severe environments!

DeoxIT® Fader F-Series - Lubricate & protect conductive plastic and carbon compound faders!

12. Shipping and Additional Information:

Hazardous: ORMD
VOC (%): Part No. D5S-6, 75% (588 g/L)





Audio/Video



Computers



Automotive



Communications



Marine



Electrical



Energy



Photography



Security



Medical



Avionics

13. Other Information:

RoHS Compliant:

YES

VOC Compliant:

YES

MSDS Link, D5S-6

<http://caig.com/material-safety-data-sheets/>

DeoxIT® Product Sheet:

<http://caig.com/technical-data/>

CAIG Essential Guide:

<http://caig.com/product-literature/#toggle-id-1>

WHY DeoxIT® is Different:

<http://caig.com/product-literature/#toggle-id-5>

14. MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, neither CAIG Laboratories, Inc., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. All materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist. All service performed on internal parts and equipment should be provided by qualified technicians.

15. Contact Information:



Website: www.caig.com
www.deoxit.com

General email: info@caig.com

Technical email: tech@caig.com

North America (Headquarters):

CAIG Laboratories, Inc.

12200 Thatcher Court
Poway, CA 92064 USA

Tel: (858) 486-8388

Fax: (858) 486-8398

Distributors (Domestic & International):

<http://store.caig.com/s.nl/sc.15/f>



CAIG Laboratories, Inc.

12200 Thatcher Court, Poway, CA 92064 U.S.A.

P: 858/486-8388 | **E:** info@caig.com

WEB: www.caig.com | www.deoxit.com

